

# AirComp

## Laboratory Air Compressor





TECHNICAL FEATURES	AirComp
FLOW RATE*	20 SLPM
TECHNOLOGIES EMPLOYED	Oil Free Piston Compressor
OUTPUT PRESSURE	0 to 8 barg / 0 to 116 psig
AIR CHARACTERISTICS	Particulate $\leq$ 0.01 microns Moisture $\leq$ 3°C dew point STP
ELECTRICAL SUPPLY	115 VAC $\pm$ 10%, 60 Hz 230 VAC $\pm$ 10%, 50 Hz
INDEX OF PROTECTION	IP20
OPERATING TEMPERATURE	5°C to 40°C / 40°F to 100°F
ENVIRONMENTAL MOISTURE	$\leq$ 80%
MAX ALTITUDE	2000 m or 6560 ft above sea level
DIMENSIONS	15.8" + 2.8" (H) CPU x 14.9" (W) x 20.8" (D) 40 cm + 7 cm (H) CPU x 38 cm (W) x 53 cm (D)
WEIGHT	88 lbs / 40 kg
ADDITIONAL FEATURES	
	Stackable
	CPU optional
	CAN-BUS optional
	Air dryer membrane included
ACCESSORIES	
	4 point pressure regulator kit
	Installation kit
	Parallel connection kit

\*Measured at standard conditions



**PROTON**  
ON SITE

PD-0600-0077 Rev. B.  
© 2010 Proton OnSite. All Rights Reserved.  
Proton, Proton OnSite, Proton Energy Systems, HOGEN, and the Proton symbol are trademarks of Proton Energy Systems, Inc. d/b/a Proton OnSite.

